



<http://energywind.ru>



## Trojan Battery –

85- , Trojan Battery

6 12

Trojan

Trojan Maxguard®

Alpha Plus®.

Deep-Cycle Gel™

Trojan Deep-Cycle Gel

Trojan

:

Trojan,

*Clean energy for life™*

<http://energywind.ru/katalog/gel-akkumulyatory>

BCI GROUP SIZE		A		B		( . )	C			
		@25 A	@75 A	5	20				D	
<b>6 V</b>										
GC2	T-605	383	105	175	210	1,3,4,5	264	181	276	26
GC2	T-105	447	115	185	225	1,3,4,5,9	264	181	276	28
GC2	T-105 Plus	447	115	185	225	1,2,4	264	181	272	28
GC2	T-125	488	132	195	240	1,3,4,5,9	264	181	276	30
GC2	T-125 Plus	488	132	195	240	1,2,4	264	181	272	30
GC2H	T-145	530	145	215	260	1,3,4,5	264	181	295	33
GC2H	T-145 Plus	530	145	215	260	1,2,4	264	181	292	33
DIN	TE35	500	135	200	245	4	244	191	276	31
901	J250G	475	130	195	235	5	292	178	302	30
901	J250P*	540	135	215	250	6	297	178	292	33
902	J305E-AC	645	160	250	305	5	311	178	365	38
902	J305G-AC	678	175	258	315	5	311	178	365	40
902	J305P-AC*	711	195	271	330	6	295	178	365	44
902	J305H-AC*	781	215	295	360	6	295	178	365	45
903	L16E-AC	766	185	303	370	5	311	178	432	46
903	L16G-AC	789	200	320	390	5	311	178	432	49
903	L16P-AC*	850	220	344	420	6	295	178	424	52
903	L16H-AC*	935	245	357	435	6	295	178	424	57
<b>12 V</b>										
24	24TMX	140	36	70	85	3,9	286	171	248	21
27	27TMX	175	45	85	105	3,9	324	171	248	25
27	27TMH	200	51	95	115	3,4,5,9	324	171	248	28
30H	30XHS	225	57	105	130	3,4,5,9	355	171	256	30
30H	31XHS	225	57	105	130	7	330	171	241	30
N/A	J150	280	70	120	150	2	351	181	283	38
N/A	J150 Plus	280	70	120	150	1,2,4	351	181	283	38
921	J185E-AC	312	82	144	175	5	394	178	371	46
921	J185G-AC	324	93	152	185	5	394	178	371	48
921	J185P-AC*	380	104	168	205	6	381	178	371	52
921	J185H-AC*	440	121	185	225	6	381	178	371	58
N/A	DC-500ML	1050	272	361	450	4,9	489	270	425	151
<b>36 V</b>										
N/A	18DC-500ML	1050	272	361	450	10	895	486	425	447
<b>6 V DEEP-CYCLE GEL</b>										
GC2	6V-GEL	394	-	154	189	5	260	181	276	31
DIN	TE35-GEL	-	-	180	210	4	244	190	276	31
<b>12 V DEEP-CYCLE GEL</b>										
24	24-GEL	147	-	66	77	5,6	276	171	236	24
27	27-GEL	179	-	76	91	5	324	171	234	29
31	31-GEL	200	-	85	102	5	329	171	245	31
DIN	5SHP-GEL	-	-	110	125	4	345	171	283	39

A. 27°C 1.75 / . . . . . \* (Polyon™)

B. 27°C 20 30°C 5 1.75 / . . . . .

C. MIN 12.7

D.

